DURO Floor & Cabinet

Website: www.durofloorusa.com

Specifications for Acoustic Sound Insulation Underlayment

Acoustic Sound Underlay provides a superb sound barrier when installed under laminate flooring, engineered wood, or hardwood floors. Acoustic Sound absorbs and reduces the transmission of noise associated with normal foot traffic, further enhancing the acoustic ambiance of the space in which it is installed. Acoustic Sound should be installed in accordance with the flooring manufacturer's published instructions. This product is designed for floating floors, glue in, snap in, or double glue installation.

- Materials - High Density Natural Rubber
- Color - Green
- Roll Size - 39.37 " ×366.15 " (100SQ.ft.roll)
- Density - pcf - 49lbs.
- Thickness (in inches) - 0.25mm/0.10 (+/-5% Manufacturing tolerance)
- Brand name - Republic
- Mold and Mildew Resistant
- Guardian Anti-Microbial
- Non-allergenic
- Facing-Top: Polyester Foil
- Facing-Bottom: Polyester non-woven
- 46 lbs. Shipping Weight
- 98% Moisture Resistance (ASTM d-1667)
- Impact Sound Transmission
- Class (IIC)= 71
- ASTM-E492-90(ASTM-E989-89)
- Sound Transmission Loss
- Class (STC)= 73
- ASTM-E90-02(ASTM-E413-87)
- "R" Value - 3.19(ft2-f-hr/Btu-in)